Phone: +61 2 9818 2000
Email: sales@chapmanmarinegroup.com.au
Website: https://www.chapmanmarinegroup.com.au/
Suite 2, Sydney Boathouse 2 Waterways Court Rozelle NSW 2039

## Boat Details

| | | | |
|---|---|---|---|
| Price | POA | Boat Brand | Mercury |
| Model | 300 HP Pro XS | Length | 0.00 |
| Year | 2021 | Category | Boat Engines and Outboards |
| Hull Style | | Hull Type | |
| Power Type | | Stock Number | 0 |
| Condition | New | State | New South Wales |
| Suburb | ROZELLE | Engine Make | Mercury |

## Description

The 300hp Pro XS provides hard-charging performance to put you out front and keep you there. Pro XS is the choice of tournament anglers and performance enthusiasts who don't like coming second. Mercury V-8 Pro XS models transform every drop of fuel into performance delivering class leading fuel economy at cruising speed and wide-open throttle. Advanced Range Optimisation (ARO) utilises closed-loop fuel control to precisely adjust the fuel mixture and deliver the best possible efficiency. All Pro XS FourStroke models now come with a 3+3=6 Year factory warranty.ENGINE DETAILS

An unmatched combination of speed, fuel economy and low cost of ownership. Great for bass and multi-species fishing boats.SPECIFICATIONS - 300
HP / kW
• 300 / 224

Engine type
• V-8

MidSection
• Conventional MidSection

Displacement (CID/CC)
• 279 CID

Displacement (L)
• 4.6L

Cylinder Configuration
• V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM
• 5600-6200

Air induction
• Performance-Tuned Long-Runner Intake Manifold

Fuel induction system
• Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt
• 85-amp (1071 Watt) with Idle Charge

Recommended fuel
• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil
• NMMA Certified FCW SAE 10W-30

Engine protection operator warning system
• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology
• Yes

Starting
• Electric Start with SmartStart Protection

Controls
• Remote Mechanical or Digital Throttle & Shift (DTS)

Steering
• Hydraulic (standard)
• Power (optional)

Shaft length
• 20" / 508 mm

• 25" / 635 mm

Gearcase ratio
• 1.75:1

Dry weight *Lightest model available
• 505 lbs / 229 kgs

CARB star rating
• 3

Bore and stroke
• 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition
• SmartCraft PCM 112 Digital Inductive

Cooling system
• Water-cooled with thermostat

Gear shift
• F-N-R

Gearcase options
• 20": TorqueMaster
• 25": 5.44"

Trim system
• Power trim and tilt

Exhaust system
• Through prop

Counter Rotation
• Available

Color
• Phantom Black

Lubrication system
• Wet sump

Oil Capacity
• 7.0 Quarts / 6.6 Liters

Maximum Trim Range
• 20° (-6° to 14°)

Maximum Tilt Range
• 73° (-6° to 67°)

## Engine Details

| | |
|---|---|
| Engine Make | Mercury |
| Displacement | 4.6 |
| Horse Power | 300 |