



Website: https://www.chapmanmarinegroup.com.au/

Suite 2, Sydney Boathouse 2 Waterways Court Rozelle NSW 2039

Boat Details

Hull Style

Power Type

Price POA Boat Brand Mercury
Model 90 HP Sea Pro Fourstroke Length 0.00

Year 2021 Category Boat Engines and Outboards

Hull Type

Stock Number

0

Condition New State New South Wales

Suburb ROZELLE Engine Make

Description

Mercury Seapro 90HP Fourstroke - These commercial outboards are designed to work as hard as you do...engineered to be ultra tough working partners for anyone making their living on the water. Every SeaPro features unique components to cope with the additional demands of professional operation. Whatever your job there's a specific FourStroke of TwoStroke Mercury SeaPro model that's up to the task. HP / kW

• 90 / 67

Engine type

- 8-valve single overhead cam (SOHC)
- Inline 4

Displacement (L)

• 2.1

Full throttle RPM

• 5000-5500

Air induction

• Performance-Tuned Scroll Intake Manifold

Fuel induction system

• Computer Controlled Multi-Port Electronic Fuel Injection (EFI)

Alternator amp / Watt

• 35 amp / 441 watt with water-cooled voltage regulator

Recommended fuel

• Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

• NMMA Certified FCW 25W-40 Synthetic Blend

Engine protection operator warning system

• SmartCraft Engine Guardian

Compatible with SmartCraft digital technology

Yes

Starting

• Smart Start Electric

Controls

Mechanical throttle & shift

Steering

- Big Tiller
- Dual Cable Mechanical
- Hydraulic

Shaft length

- 20" / 508 mm
- 25" / 635 mm

Gearcase ratio

• 2.38:1

Dry weight *Lightest model available

• 363 lbs / 165 kg

Bore and stroke

• 3.5 x 3.2" / 90 x 81 mm

Ignition

SmartCraft ECM 70 Digital Inductive		
Fuel system • Electronic Fuel Injection (EFI)		
Cooling system • Water-cooled with thermostat		
Gear shift • F-N-R		
Trim system • Power Tilt • Power Trim		
Exhaust system • Through prop		
Shallow water trim range (degrees) • 20		
Color • Phantom Black		
Lubrication system • Integrated Dry Sump		
Oil Capacity • 5.5 qts / 5.2 l		
Maximum Trim Range • 22° (-6° to 16°)		
Maximum Tilt Range • 70° (-6° to 64°)		
Features Horse Power (hp)	90	

Engine DetailsHorse Power

90